

ComColor FT 5000

Ultra High-Speed
Full-Color Inkjet Printers



HIGH-SPEED

A4 colour printing

Full-color A4 printing



Print speed
100 ppm



Print size
A4



Full color



3 trays



Low energy
consumption



Environmental
certification

Where environmental friendliness

Cleaner and Friendlier

RISO's environmental ethos is—and always has been—to design and develop products that exert the smallest possible impact on the environment throughout their lifecycles.

Low energy consumption

- Operates on standard power
- Does not generate heat like toner printers

360w (During printing)

No harmful emissions

- No toner particle emissions

No ozone

Low resource consumption

- High-durability design means few replacement parts
- Inkjet printers do not require consumables (drum, fuser unit, etc.) like toner printers

Less waste

Low TEC* value

- Low energy consumption even during continuous high-speed printing
- Energy efficiency vastly superior to other printers operating at same speed

1.55kWh/week

*TEC value: Typical Electricity Consumption. This value represents electricity consumed in one week, and is based on the international ENERGY STAR** standard.

**The International ENERGY STAR Program is an international energy-saving program implemented in the United States, Canada, Japan, EFTA, Switzerland, and Taiwan.

Richer and Fuller

High-speed HS7000 Scanner

- 100ppm (A4 LEF)
- Scan sizes up to A3
- Simultaneous duplex scanning
- Compatible with various file formats (PDF, PDF/A, TIFF, JPEG)

Face Down Finisher

- ComColor finisher exclusively for offset stacking and stapling finished prints



and productivity unite.

Smarter and Faster

Enjoy enhanced time efficiency, optimized TCO, and consistently high quality that only RISO can deliver.

High speed, high productivity <ul style="list-style-type: none">• First print time of less than 5 seconds• 1,000 sheets in just 10 minutes	100ppm (A4SEF)
High reliability <ul style="list-style-type: none">• Simple inkjet mechanism is durable and requires few replacement parts• Low maintenance	Less downtime
High usability <ul style="list-style-type: none">• Intuitively designed user interface• 90-degree tilt panel for easy viewing	Simple operation

Lower and Higher

High cost efficiency <ul style="list-style-type: none">• Proprietary ink and color profile development enable high quality at low running cost• Short printing time means reduced labour and electricity costs	Low running cost
High image quality <ul style="list-style-type: none">• Piezo drop-on-demand print heads• Fast-drying oil-based ink• New, higher black density	Enhanced appearance
High media flexibility <ul style="list-style-type: none">• 46gsm-400gsm (when optional accessories attached)	Lightweight to heavyweight paper, as well as envelopes



← **Multifunction Finisher**
Stapling, punching, folding, stacking, and booklet making in A4 short edge configuration only.

Postscript RIP for higher productivity

- Compatible with wide range of data formats
 - Queue settings
 - Tray selection per page
 - Form overlay

ComColor FT 5000 Specifications

Print Type		Line-type inkjet system	
Ink Type		Oil-based pigment ink (Cyan, Magenta, Yellow, Black)	
Print Resolution		Standard: 300 x 300 dpi Fine: 300 x 600 dpi	
Number of Gray Levels		For each CMYK color (11 gray levels)	
Data Processing Resolution		Standard: 300 dpi x 300 dpi Fine: 600 dpi x 600 dpi Line smoothing: 600 dpi x 600 dpi	
Warm-up Time		2 min. 30 sec. or less (at room temperature of 23°C)	
First Print Time *1		5 sec. or less (A4)	
Continuous Print Speed *2	A4	Simplex: 100 ppm	Duplex: 50 sheets/minute (100 ppm)
Paper Size	Standard Tray	Maximum: 340 mm x 550 mm *3	Minimum: 90 mm x 148 mm
	Feed Tray	Maximum: 297 mm x 432 mm	Minimum: 182 mm x 182 mm
Printable Area		Maximum: 210 mm x 544 mm	
Guaranteed Print Area *4		Standard: Margin width of 5 mm	Maximum: Margin width of 3 mm
Paper Weight	Standard Tray	Simplex: 46 gsm to 210 gsm *5	Duplex: 46 gsm to 210 gsm *5 for A4/46 gsm to 104 gsm for A3, B4 (JIS)
	Feed Tray	Simplex/Duplex: 52 gsm to 104 gsm	
Paper Tray Capacity	Standard Tray	Height up to 110 mm	
	Feed Tray	Height up to 56 mm (2 trays)	
Output Tray Capacity		Height up to 56 mm	
Page Description Language		RISORINC/C IV	
Supported Protocols		TCP/IP, HTTP, HTTPS (TLS), DHCP, FTP, LPR, IPP, SNMP (SNMP v1), Port 9100 (RAW port), IPv4, IPv6, IPSec (IKEv1)	
Supported Operating Systems	Standard	Microsoft®: Windows®, Windows Server® *6	
	Optional *7	Mac: macOS *6 Linux®: Compatible with PPD only	
Network Interface		Ethernet 1000BASE-T/100BASE-TX/10BASE-T×2 Channel	
Memory Capacity		4 GB	
Hard Disk *8	Capacity	500 GB	
	Available Space	Approx. 430 GB	
Operating System		Linux	
Power Source		AC 100-240 V, 10.0-5.0 A, 50-60 Hz	
Power Consumption		Max. 1,000 W Ready *9: 95 W or less Sleep *10: 2 W or less Stand-by: 0.4 W or less	
Operating Noise		64dB (A) or less at printing	
Operating Environment		Temperature: 15°C to 30°C Humidity: 40% to 70% RH (non-condensing)	
Dimensions (W x D x H)		In use: 1,030 mm x 735 mm x 1,115 mm With cover and tray closed: 775 mm x 710 mm x 970 mm	
Weight		Approx. 135 kg	
Dimensions When Operating (W x D x H)		With the front cover open and the operation panel in the upright position: 1,185 mm x 1,225 mm x 1,115 mm	
Accessories		Scanner HS7000, Face Down Finisher F10, Multifunction Finisher FG20, Auto-Control Stacking Tray II, Wide Stacking Tray, ComColorExpress RS1200C, PS Kit FG10, IC Card Authentication Kit II.	

Specifications are subject to change without notice.

- *1 Within 10 minutes after the last print job.
 *2 When using plain paper and recycled paper (85 gsm), and standard density setting. Chart used: Print measurement pattern [Color measurement sample 2 (JEITA standard pattern J6)].
 The continuous print speed varies depending on the type of optional output equipment connected.
 Face Down Finisher: Without offset: 100 sheets/minute (A4 Simplex), Offset output: 82 sheets/minute (A4 Simplex).
 *3 When using duplex print: 340 mm x 460 mm.
 *4 The guaranteed area when printing images is the area enclosed within 5 mm of the edges of the paper. The margin when printing envelopes is 10 mm.
 *5 Duplex printing is not guaranteed with thick paper the weight of which is greater than 104 gsm.
 *6 For the OS version, please refer to the RISO Website or contact your local sales representative.
 *7 Optional PS Kit FG10 or ComColor Express RS1200C is required.
 *8 One gigabyte (GB) is calculated as 1 billion bytes.
 *9 Without printing and temperature adjustment operation.
 *10 When setting [Power Consumption (in sleep)] to [Low].



ComColor FT Ink Cartridges

Colors: Black, Cyan, Magenta, Yellow

Environmental Certifications



RISO, and ComColor are trademarks or registered trademarks of RISO KAGAKU CORPORATION. Mac and macOS are trademarks of Apple Inc., Microsoft, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries. Other corporate names and/or trademarks are either registered trademarks or trademarks of each company, respectively.



RISO UK Ltd
 610 Centennial Park, Centennial Avenue,
 Elstree, Hertfordshire, WD6 3TJ
www.riso.co.uk